NOTICE OF REVISION (NOR) THIS REVISION DESCRIBED BELOW HAS BEEN AUTHORIZED FOR THE DOCUMENT LISTED			6 04 05	Form Approved OMB No. 0704-0188
Public reporting burden for this collection of information is estimated to average 2 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jafferson Davis Highway, Suite 1204, Arlington VA 22202-4302, and to the Office of Management and Budget. Paperwork Reduction Project (0704-0188), Washington DC 20503. PLEASE DO NOT RETURN YOUR COMPLETED FORM TO EITHER OF THESE ADDRESSES. RETURN COMPLETED FORM TO THE GOVERNMENT ISSUING CONTRACTING OFFICER FOR THE CONTRACT/PROCURING ACTIVITY NUMBER LISTED IN ITEM 2 OF THIS FORM.				2. PROCURING ACTIVITY NO. R06A2004 3. DODAAC
4. ORIGINATOR	b. ADDRESS (Street, City, State, Zip Code)		5. CAGE CODE	6. NOR NO.
TYPED NAME (First, Middle Initial, Last) U.S. ARMY ARDEC			19200	1 of 3
THOMAS MUELLER	BLDG 355N, AMSRD-AAR-AEM-D, NJ		7. CAGE CODE	8. DOCUMENT NO.
9. TITLE OF DOCUMENT	PICATINNY ARSENAL, N.J. 07806		19200	9345325 11. ECP NO.
PLUG ASSEMBLY, LIFTING, UNIV			b. NEW	R06A2004
12. CONFIGURATION ITEM (OR SYSTEM) TO WHICH ECP APPLIES 155MM ARTILLERY				
13. DESCRIPTION OF REVISION				
REVISE NOTE 12:				
FROM: "12. FINAL PROTECTIVE FINISH:- LUSTERLESS YELLOW, COLOR NUMBER 33538 OF FED-STD -595.  OVERSPRAY PERMITTED ON OUTER FACE OF GASKET GROOVE PROVIDED ALL SUBSEQUENT GAGING REQUIREMENTS ARE MET. "				
TO: "12. FINAL PROTECTIVE FINISH: COAT INDICATED SURFACE WITH AMMUNITION TOPCOAT IAW FINISH 20.2 OF MIL-STD-171 (TYPE II OF MIL-DTL-11195), LUSTERLESS YELLOW, COLOR NO. 33538 OF FED-STD-595. COATING THICKNESS SHALL BE 1.0 MIL TO 2.0 MIL. OVERSPRAY PERMITTED ON OUTER FACE OF GASKET GROOVE PROVIDED ALL SUBSEQUENT GAGING REQUIREMENTS ARE MET. "				
UPDATE REVISION BLOCK				
a. (X one) X (1) Existing document su				
(2) Revised document must be received before manufacturer may incorporate this change.				
b. ACTIVITY AUTHORIZED TO APPROVE CHANGE FOR GOVERNMENT c. TYPED NAME (First, Middle Initial, Last)				
d. TITLE Armando Herrera Conventional Ammo Division Chief SFAE-AMO-CAS	e. SIGNATURE	lundo He		f. DATE SIGNED (YYMMDD) 20060519
15.a. ACTIVITY ACCOMPLISHING REVIS	b. REVISION COMPLETE	:D (Signature)		c. DATE SIGNED (YYMMDD)